

POWERED BY **Dialog**

**Polyvinylidene fluoride material sheathed in polyamide - and plasticised with butylbenzenesulphonamide**

**Patent Assignee: ATOCHEM**

**Inventors: STRASSEL A**

#### Patent Family

Patent Number	Kind	Date	Application Number	Kind	Date	Week	Type
FR 2602515	A	19880212	FR 8611546	A	19860808	198814	B

**Priority Applications (Number Kind Date): FR 8611546 A ( 19860808)**

#### Patent Details

Patent	Kind	Language	Page	Main IPC	Filing Notes
FR 2602515	A		6		

#### Abstract:

FR 2602515 A

A material based on polyvinylidene fluoride sheathed with polyamide is improved in that the PVdF is plasticised with butylbenzene sulphonamide (I). Pref. the PVdF contains 0.5-40 wt% of (I).

USE/ADVANTAGE - PVdF pipes sheathed in polyamide are used partic in the petroleum industry. To improve its flexibility PVdF is usually plasticised with a sebacate, partic dibutyl sebacate (DBS). However, in contact with water, the polyamide sheat tends to degrade when using sebacate plasticisers. The use of (I) instead of sebacate overcomes this problem, the polyamide retaining its desirable properties.

0/0

Derwent World Patents Index

© 2005 Derwent Information Ltd. All rights reserved.

Dialog® File Number 351 Accession Number 7459739